


# HMF EXPRESS



## Knock Down 4-Sided Borrowed Light

	Glass Type	Max Exposed Area of Glazing	Max Width of Exposed Glazing	Max Height of Exposed Glazing	Glazing Bead Size	Stop Height
		(in <sup>2</sup> )	(in)	(in)		
<b>20 min</b>	Wire or Firelite Glass	6272	106 1/2	106 1/2	5/8" X 5/8"	5/8"
<b>45 min</b>	Wire Glass	500	40	54	5/8" X 5/8"	5/8"
		1200	40	40	3/4" X 3/4"	3/4"
		1296	30	54	3/4" X 3/4"	3/4"
	Firelite Glass	3325	95	95	5/8" X 5/8"	5/8"
<b>60 min</b>	Firelite Glass	3325	95	95	5/8" X 5/8"	5/8"

Requirements	Jamb Faces		Jamb Depth		Metal Gauge	
	Min.	Max.	Min.	Max.	Min.	Max.
	1 1/4"	4"	4 1/2"	14"	16	14

**Notes:** Frames can be installed with any of our UL listed Anchor Options

Compression Anchors (if used) are placed in Head & Sill

Frames with Wire Glass receive a metal UL label

Frames with Firelite Glass receive a metal UL label, and a supplemental label stating Firelite Glass and other glazing requirements

20 Minute Frame Labels are "Without Hose Stream"

Maximum Overall Width and Height = Exposed Glass Size + (Stop Height + Face Size x2)