

FLEMMING LOCATIONS.xls

3 HINGES

Hinge Size	Hinge Qty.	Opening Height	1st Hinge	2nd Hinge	3rd Hinge	4th Hinge	Strike Location AFF
4.50	3	5'	7 1/2	27 7/16	47 3/8	X	40 5/16
4.50	3	5'2"	7 1/2	28 7/16	49 3/8	X	40 5/16
4.50	3	5'4"	7 1/2	29 7/16	51 3/8	X	40 5/16
4.50	3	5'6"	7 1/2	30 7/16	53 3/8	X	40 5/16
4.50	3	5'8"	7 1/2	31 7/16	55 3/8	X	40 5/16
4.50	3	5'10"	7 1/2	32 7/16	57 3/8	X	40 5/16
4.50	3	6'	7 1/2	33 7/16	59 3/8	X	40 5/16
4.50	3	6'2"	7 1/2	34 7/16	61 3/8	X	40 5/16
4.50	3	6'4"	7 1/2	35 7/16	63 3/8	X	40 5/16
4.50	3	6'6"	7 1/2	36 7/16	65 3/8	X	40 5/16
4.50	3	6'8"	7 1/2	37 7/16	67 3/8	X	40 5/16
4.50	3	6'10"	7 1/2	38 7/16	69 3/8	X	40 5/16
4.50	3	7'	7 1/2	39 7/16	71 3/8	X	40 5/16
4.50	3	7'2"	7 1/2	40 7/16	73 3/8	X	40 5/16
4.50	3	7'4"	7 1/2	41 7/16	75 3/8	X	40 5/16
4.50	3	7'6"	7 1/2	42 7/16	77 3/8	X	40 5/16
4.50	3	7'8"	7 1/2	43 7/16	79 3/8	X	40 5/16
4.50	3	7'10"	7 1/2	44 7/16	81 3/8	X	40 5/16
4.50	3	8'	7 1/2	45 7/16	83 3/8	X	40 5/16
4.50	3	8'2"	7 1/2	46 7/16	85 3/8	X	40 5/16
4.50	3	8'4"	7 1/2	47 7/16	87 3/8	X	40 5/16
4.50	3	8'6"	7 1/2	48 7/16	89 3/8	X	40 5/16
4.50	3	8'8"	7 1/2	49 7/16	91 3/8	X	40 5/16
4.50	3	8'10"	7 1/2	50 7/16	93 3/8	X	40 5/16
4.50	3	9'	7 1/2	51 7/16	95 3/8	X	40 5/16
4.50	3	9'2"	7 1/2	52 7/16	97 3/8	X	40 5/16
4.50	3	9'4"	7 1/2	53 7/16	99 3/8	X	40 5/16
4.50	3	9'6"	7 1/2	54 7/16	101 3/8	X	40 5/16
4.50	3	9'8"	7 1/2	55 7/16	103 3/8	X	40 5/16
4.50	3	9'10"	7 1/2	56 7/16	105 3/8	X	40 5/16
4.50	3	10'	7 1/2	57 7/16	107 3/8	X	40 5/16
5	3	5'	7 1/4	27 3/16	47 1/8	X	40 5/16
5	3	5'2"	7 1/4	28.1875	49 1/8	X	40 5/16
5	3	5'4"	7 1/4	29.1875	51 1/8	X	40 5/16
5	3	5'6"	7 1/4	30.1875	53 1/8	X	40 5/16
5	3	5'8"	7 1/4	31.1875	55 1/8	X	40 5/16

Note: (1) Locations and adjustments must be verified with each manufacturer.

FLEMMING LOCATIONS.xls

3 HINGES

Hinge Size	Hinge Qty.	Opening Height	1st Hinge	2nd Hinge	3rd Hinge	4th Hinge	Strike Location AFF
5	3	5'10"	7 1/4	32.1875	57 1/8	X	40 5/16
5	3	6'	7 1/4	33.1875	59 1/8	X	40 5/16
5	3	6'2"	7 1/4	34.1875	61 1/8	X	40 5/16
5	3	6'4"	7 1/4	35.1875	63 1/8	X	40 5/16
5	3	6'6"	7 1/4	36.1875	65 1/8	X	40 5/16
5	3	6'8"	7 1/4	37 3/16	67 1/8	X	40 5/16
5	3	6'10"	7 1/4	38 3/16	69 1/8	X	40 5/16
5	3	7'	7 1/4	39 3/16	71 1/8	X	40 5/16
5	3	7'2"	7 1/4	40 3/16	73 1/8	X	40 5/16
5	3	7'4"	7 1/4	41 3/16	75 1/8	X	40 5/16
5	3	7'6"	7 1/4	42 3/16	77 1/8	X	40 5/16
5	3	7'8"	7 1/4	43 3/16	79 1/8	X	40 5/16
5	3	7'10"	7 1/4	44 3/16	81 1/8	X	40 5/16
5	3	8'	7 1/4	45 3/16	83 1/8	X	40 5/16
5	3	8'2"	7 1/4	46 3/16	85 1/8	X	40 5/16
5	3	8'4"	7 1/4	47 3/16	87 1/8	X	40 5/16
5	3	8'6"	7 1/4	48 3/16	89 1/8	X	40 5/16
5	3	8'8"	7 1/4	49 3/16	91 1/8	X	40 5/16
5	3	8'10"	7 1/4	50 3/16	93 1/8	X	40 5/16
5	3	9'	7 1/4	51 3/16	95 1/8	X	40 5/16
5	3	9'2"	7 1/4	52 3/16	97 1/8	X	40 5/16
5	3	9'4"	7 1/4	53 3/16	99 1/8	X	40 5/16
5	3	9'6"	7 1/4	54 3/16	101 1/8	X	40 5/16
5	3	9'8"	7 1/4	55 3/16	103 1/8	X	40 5/16
5	3	9'10"	7 1/4	56 3/16	105 1/8	X	40 5/16
5	3	10'	7 1/4	57 3/16	107 1/8	X	40 5/16

Subtract clearance from hinge locations & undercut from strike locations for doors

Note: (1) Locations and adjustments must be verified with each manufacturer.

(2) HMF Express is not responsible for errors resulting from using this table.